



## Clamping straps type MCA

Universal banding system for flexible ducts.

### Brand

- Sufix

### Application

- Clamps **MCA** are used for easy and quick fastening of flexible ducts in industrial or other applications.
- Automatic locking by means of a tilting housing with screw.
- Only for indoor use

### Material

- Stainless steel AISI 430 EN1.4016

### Specifications


- Constructed in accordance with DIN 3017 standards
- Width: 9 mm
- Thickness: 0,6 mm
- Screw: size 7 mm, cross slotted-hexagon head, galvanized steel (80/200 hours resistance against saline mists)

### Models

- Pre-cut length according to the diameter, range from 60 up to 660 mm

### Text for tender

- The flexible ducts shall be fastened by means of AISI 430 EN1.4016 stainless steel clamps of 0,6 mm thickness, 9 mm width, constructed in accordance with DIN 3017 standard with locking device.
- Sufix **type MCA**



MCA	Dimensions	
	Max Ø [mm]	L [mm]
MCA 60-110	110	380
MCA 60-135	135	470
MCA 60-165	165	560
MCA 60-215	215	730
MCA 60-270	270	900
MCA 60-325	325	1070
MCA 60-380	380	1240
MCA 60-525	525	1700
MCA 60-660	660	2140