

## ISW-4P

- Accessories
- 4-pole isolator switch



## 4-pole Isolator Switches type ISW-4P

Isolator switch.

Insulated 4-pole CE marked isolator switch. Suitable for disconnecting the power supply to outdoor heat pump units and air handling units. Available in small (ISW-4P-20A and ISW-4P-32A) and standard (ISW-4P-40A and ISW-4P-63A) sizes with cable gland.

### Composition

- Protection class: IP65
- M20/25 inputs up to 63A
- Handle lockable in off position
- Interlocked cover - removable in off position only
- Earth and neutral terminals included
- Standard: IEC 60947-3

| Technical data |                   |                                 |                                 |                |                |
|----------------|-------------------|---------------------------------|---------------------------------|----------------|----------------|
| TYPE           | Ampère (A) - AC21 | Capacity (kW) - AC23 A<br>240VA | Capacity (kW) - AC23 A<br>400VA | Cable capacity |                |
|                |                   |                                 |                                 | Solid (mm²)    | Stranded (mm²) |
| ISW-4P-20A     | 20                | 5.5                             | 3.7                             | 1-16           | 0,75-10        |
| ISW-4P-32A     | 32                | 11                              | 7.5                             | 1-16           | 0,75-10        |
| ISW-4P-40A     | 40                | 15                              | 11                              | 1-16           | 0,75-10        |
| ISW-4P-63A     | 63                | 22                              | 18.5                            | 1-16           | 0,75-10        |

Utilization category according to IEC 60947-3-1:

- AC-21: Switching of resistive loads, including moderate overloads

- AC-23: Switching of motor loads or other highly inductive loads

| Dimensions |            |            |             |
|------------|------------|------------|-------------|
| TYPE       | Width (mm) | Depth (mm) | Height (mm) |
| ISW-4P-20A | 100        | 120        | 125         |
| ISW-4P-32A | 100        | 120        | 125         |
| ISW-4P-40A | 114        | 135        | 175         |
| ISW-4P-63A | 114        | 135        | 175         |